

## Integral Jacks

Capacity 10 - 50 ton | Stroke 150 - 155 mm | Max. Working Pressure 700 bar

### Features / Application

- Construction : Graded steel
- Fully serviceable
- Pumping handle included on all models
- Built-in factory set Safety relief valve to prevent over load
- Ground & plated plungers
- Low handle effort reduces operator fatigue



OIJ Series - O Orione | Integral J Jack 10 Capacity - ton 150 Stroke - mm

Rated capacity (ton)	Stroke (mm)	Additional screw extension (mm)	Model	A Closed height (mm)	B Extended Height (mm)	C Bottom plate size (mm)	D Ram dia. (mm)	E Saddle dia. (mm)	Saddle Max. Tilt Angle	Pump Speed	Weight (kg)
10	150	100	OIJ10-150	240	390	130x160	45	35	5°	Single Speed	18
20	155	110	OIJ20-155	275	430	160x180	55	50	5°	Single Speed	22.5
30	150	120	OIJ30-150	285	435	170x200	65	60	5°	Single Speed	30
50	150	120	OIJ50-150	300	450	210x245	85	74	5°	Two Speed	49

- Higher capacity and customized solutions on request.
- Specifications are subject to change due to continual improvement.
- Capacity and Stroke specified are maximum safe limits. Use at 80% of rating as safe practice.